

that excites

## NISSAN MOTOR OIL FULLY SYNTHETIC 5W-30 C4

Very high performance lubricant synthetic technology, intended for lubricating light vehicles engines, specially formulated to ensure compatibility with post-treatment systems.

| CHARACTERISTICS  | <ul> <li>Supports fuel economy</li> </ul>   |  |                                 |                       |  |
|------------------|---|--|---------------------------------|-----------------------|--|
|                  | <ul> <li>Compatible with post-treatment systems that enables high reduction of pollutant emissions, thanks to low rate sulfur, ashes and phosphorus (low SAPs)</li> <li>Ensures an outstanding engine longevity, thanks to a high oxidation resistance</li> <li>Confers to the engines an excellent global wear protection, thanks to its latest technology. Ensures maximum engine cleanliness, thanks to very good detergent and dispersion properties</li> </ul> |  |                                 |                       |  |
| CLIENTS BENEFITS | - A better environment<br>- Ensured performance<br>- Excellent engine prot<br>- Fuel Economy  | of the lubricant over  |                                 |                       |  |
| PERFORMANCE      | <ul><li>ACEA: C4, performance</li><li>NISSAN (all vehicles equ</li></ul>  |  |                                 | 9I)                   |  |
|                  | <ul> <li>The most severe jour</li> <li>« Vigorous » driving,</li> <li>Recommended in partiemission reduction</li> <li>Particularly adapted to N</li> <li>For all driving styles, par<br/>Refer to the maintenance</li> </ul>  | all times of year<br>cular for the engines re<br>issan recent vehicles equ | ipped with Diese<br>high speeds | el Particulate filter |  |
| USES             | - Most recent technolo  |  |                                 |                       |  |

|                     | Methode    | Unites | SAE Grade 5W30 |
|---------------------|------------|--------|----------------|
| Viscosity at 40°C   | ASTM D445  | mm²/s  | 73             |
| Viscosity at 100 °C | ASTM D445  | mm²/s  | 12.3           |
| Viscosity index     | ASTM D2270 | -      | 165            |
| Pour Point          | ASTM D97   | °C     | -39            |
| Flash Point         | ASTM D92   | °C     | 230            |
|                     |            |        |                |

The typical characteristics mentioned represent mean values

This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.